



IBERICA HAV

C6Y13 - IMO 9210012
 General Dry Cargo ship built 1999
 Bahamas Flag; P&I by Gard; GL 13/3
 +CARGOSHIP DEEPSEA+MACH,BGR

Mobile captain: +47 469 35 485
 Satellite phone: +8 7077 315 7685
 E-Mail 1: iberica@hav.amosconnect.com
 E-Mail 2: iberica@hav.no



GT	1599	Service speed (knots)	Abt 9	Tank capacities:		
Timbercapacity-LP	Abt 2800cbm	Fesi fitted	yes	Distance from keel to top with antenna	20,0m	
NT	691	Consumption main engine (ltr/24hrs)		Water ballast	1378 cbm	
LOA	87,92m	with A/E	Abt 3500	Distance from tank top to top of hatch		
Beam	11,40m	Ventilation - airchanges/hours	6	coamings	5,5m	
Draft summer	3,68m	Port consumption (ltr/24hrs)	200	Gasoil	114 cbm	
DWT	2219 mts	Hatch type	Gantry - multi stack	Mean draft of ship in heavy ballast (m) (FW)	2,75m	
DWCC-Summer	Abt 2150 mts	Main engine type / output	MAK 6M20 / 749KW	Freshwater	32 cbm	
DWCC - Winter	Abt 2070 mts	Hatch dimension /hatches closed/, (m)	61,8 x 9,27m			
Capacity of holds bale	3 020 cbm	Propeller	Fixed			
Capacity of holds bale	106 632 cbft	Max permissible loading on hatch covers (t/m ²)	1,6	Bulkheads	Frame	
Capacity of holds grain	3 020 cbm	Hold dimenions L x B x H (m)		Pos 1	44-58	cbft from aft
Capacity of holds grain	106 632 cbft	No narrowings, fully boxed	60,2 x 9 x 5,5m	Pos 2	33-58	14.072
Rudder type	Becker	Max permissible loading on tanktop (t/m ²)		Pos 3	44-85	25.277
Min airdraft in heavy ballast	6,1m	Tanktop strengthened for heavy cargoes.	15	Pos 4	33-85	42.356
Bow thruster	Yes	Height of hatchcover motors into the hold	n/a	Pos 5	44-109	53.543
Max airdraft in heavy ballast	19,50m	Distance from waterline fully ballasted		Pos 6	33-109	67.475
Depth moulded	5,40m	top of hatch coaming /hatches closed/, (m)	5,88	Pos 7	44-128	78.681
Rhine/Seine/Saimaa	yes	Container capacity (TEU)	0	Pos 8	44-136	87.369
		Height of hatch coaming/hatches closed/,	2,5m	Pos 9	33-128	95.427
				Pos 10	33-136	98.574
						106.633